



AC 880

Standby 880 kVA

0 00000000 00000000T 0000 00 0 00000000

0 0000T 000 Cummins
0 00T 0000T 00Mecc Alte
0 00T 00 0 3 0000000T 00 00 0000000000
T 0000000000

0 0 0000T 0000T 000000000000 000000T 0000

Manufacturer		Cummins
Model		QSK 23 G3
0 00000 00000000000000T 00000000 00 000T 0		000000000 0000 000000000T 0 >00000000+ 3 @
0 0000 000000000000000	L	23,150
0 000 0T 000000000000 00	0 0 0	170 x 170
0T 00000000 0T 00		16,0:1
0 00 00000000 0000000T 0 0000 0000	00000 0000	1500
0 0 000T 000 0000000 00	L	103,00
0 0000 000000 000 0 0000 00000T 0	L	120,00
AbsorbedAirDischargeReSourceKey.Text	0 000 0000	53,30
0 000T 00000000000000000000T 000000T 0 0000000000T 0000 00 000 0000	0 000 0000	625,80
0 000T 00000000000000000000T 0000 000000000T 0T 00	0 000 0000	147,80
0000 00000T 00000 0000000	° C	543,00
0 000T 00000000000000T 00 0		24 V d.c.
0 00000T 00000000	Load 0 00000	00000000 00000000 00000000 0000T 0000 0000T 0000 0000T 0000 161,00 121,00 85,00

0 000000T 0000T 0000

0 000000000T 0000		Mecc Alte
0 000000		ECO 43-1SN/4
0 000T 00	Hz	50
0 00 000T 0	00T 0	800,00
&R V 00		0,80
0 000000T 0000 00		3
0 000000 000000000T 0000T 0000000 0	0	400/230
0000	A	1154,00
Temperature		H

0 0 0000 0000 0000000

0T 000T 00 0T 0000	0000	0 0000000 0 00	0 000000	00 00T 0000 0 00	00 000T 0T 0000000000000000
	0000	0 000	0 000	0 000	L
AC 880	5950,00	3950,00	1705,00	2225,00	1500,00
00T 0000 00 000T 0000	0000	0 0000000 0 00	0 000000	00 00T 0000 0 00	00 000T 0T 0000000000000000
	0000	0 000	0 000	0 000	L
AK 90	9100.00	6500	2200	2353	850

[illegible]

T

0 00000000 0000
 0 00000000 0000000000 0000
 0 00000000000000000000 000000
 0000 00000000; 0000000000 0000 000000000000 0
 0000 00000 00000000000000000000
 0 0000000 0000000000; 00; 0000 0000
 0 0000000 0000
 0000000000 00
 0 0000000 00000000 0 00 0 0
 000000 00 00 00
 0000; 00
 00000000000 0000000
 000
 0 0
 000 0 00000
 000 00000000 00000000 000000
 0 000000000000; 0000000000; 0000 00
 0 000 0000 000000000000000000 00 0
 0 0000000 00000000 0 00 0 0
 0 0000 00 00

[illegible][illegible][illegible][illegible]

070000070

[illegible][illegible][illegible]

Cummins
Mecc Alte
3
t



- 1 Steel structure made from steel sheet and steel profiles.
- 2 canopy and panels made from powder coated sheet steel.
- 3 Emergency stop push button.
- 4 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 5 Cables out locations are under or back of the canopy.
- 6 Corrosion-resistant locks and hinges.
- 7 oil could be drained via valve and a hose
- 8 Exhaust system in the canopy.
- 9 special large access doors (marine type) for easy maintenance
- 10 Fuel tank is at front of the canopy ,easy access to the fuel tank via lockable door
- 11 Lifting points similar to ISO container , located on each top corner of the canopy
- 12 the cap on the canopy provides easy access to radiator cap.
- 13 sound proofing materials
- 14 Integrated ladder built in to side of the canopy allows access to the top of the canopy.

of the canopy.

T

of the canopy.

[illegible][illegible]

□ □□□□□	□ □ □	2200
□ □□□□□□ □ □	□ □ □	6500
□□ □□□□□ □ □	□ □ □	2353
□ □ □□□□□ □□□□□□□□□□□□	L	850